

| Technical Specifications | PC48.0W-02009 | PC48.0W-08009 | PC48.0W-01009 |
|---------------------------------|----------------------|----------------------|----------------------|
| Rated Current | 220mA | 220mA | 220mA |
| Class | A+ | A+ | A+ |
| Consumption | 48kWh/1000h | 48kWh/1000h | 48kWh/1000h |
| Driver service Life | 20.000 hours | 20.000 hours | 20.000 hours |
| Panel Service Life | 50.000 hours | 50.000 hours | 50.000 hours |
| CRI | ≥ 80 | ≥ 80 | ≥ 80 |
| Power Factor | > 0.95 | > 0.95 | > 0.95 |
| Heating Time | < 1sec. | < 1sec. | < 1sec. |
| Operating Voltage Range | 150 - 260VAC | 150 - 260VAC | 150 - 260VAC |
| Rated Voltage | AC230V 50Hz | AC230V 50Hz | AC230V 50Hz |
| Rated Power | 48 W | 48 W | 48 W |
| Lumen | 4100 | 4100 | 4100 |
| Luminous Colour | Warm White | Daylight | Cold White |
| Chrominance Signal | WW | NW | CW |
| Colour Temperature | 3000K | 4000K | 6500K |
| Body Colour | White/RAL 9016 | White/RAL 9016 | White/RAL 9016 |
| Body Material | Aluminum | Aluminum | Aluminum |
| IP Definition | IP20 | IP20 | IP20 |